

PRODUCT SPECIFICATION DATA

DESCRIPTION:

The DEL600 is a decorative, low-profile, architectural emergency light.

ELECTRICAL/ILLUMINATION

- Energy-efficient, LED technology
- Dual 120V/277V
- LVD (low voltage disconnect) prevents battery from deep discharge
- Long-life, maintenance free, rechargeable NiCd battery
- Internal solid-state transformer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination
- Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours
- Batteries pro-rated for five years
- Charge rate/power "ON" LED indicator light and push to test switch for mandated code compliance testing
- Self-diagnostic standard

HOUSING

- Die-cast aluminum housing; sealed and gasketed
- Mirror-bright reflector and prismatic polycarbonate lens
- Surface mount via easy connect back plate fits most standard size junction boxes and snaps into place making internal electrical connections
- Five year warranty on all electronics and housing

WARRANTY & LISTINGS

- UL Listed standard for wet locations (0°-50°C/32°F-122°F).
CW option UL listed for wet locations (-20°-50°C/-4°F-122°F).
- Five year warranty on all electronics and housing. Batteries pro-rated for five years.
- Meets UL924 NFPA101 Life Safety Code, NEC, OSHA, Local and State Code.

Electrical information

DEL600LED	120V	2.7W	0.026A
	277V	2.8W	0.012A
DEL600LED-CW	120V	2.9W	0.031A
	277V	3.0W	0.014A

ORDERING INFORMATION (Example: DEL600)

Series **DEL600**

Type: _____

Catalog #: _____

Project: _____

Date: _____

