

# DRD3

## Adjustable Recessed LED Downlight

Perfect for specialized designs  
like sloped ceilings

360° rotation enables precise  
directional aim

Won't cross the ceiling plane,  
even when tilted



## Specs at a Glance

Application	New Construction, Remodel, Retrofit
Housing	4", 5", 6", 6" Shallow
Adjustment	360° directional aim, 40° tilt
Lumen Output (Power)	750 lm (12.0W), 1000 lm (14.7W)
Color Quality	90+ CRI, 2-step SDCM
CCT Options	2700K, 3000K, 3500K, 4000K
Optics	Spot (23°), Flood (42°)
Module Finish	White, Black, Custom
Lifetime (L70)	50,000 hrs
Input Voltage	120/277V
Dimming	Down to less than 5% for TRIAC/ELV at 120V, 1% for 0-10V or Lutron® Hi-Lume® 1% at 120/277V
Emergency Lighting	Optional Emergency LED Driver for lighting up to 90 minutes in event of power failure
Trim Shape	Round, Square on Round
Trim Style	Smooth, Baffle
Trim Finish	White, Black, Silver (silver reflector, white flange), Custom
Listings	cULus Listed, ENERGY STAR® qualified, California Title 24 2016 JA8 compliant, UL Listed for Damp Location, IC rated, ASTM E283 certified Air Tight
Warranty	5 years

# Product Selection Example

See spec sheets for complete ordering information and options

## FRAME-IN KIT (Product Code Example: DRDH + N + IC + 4 = DRDHNIC4)

PRODUCT CODE	APPLICATION	IC/NON-IC	APERTURE	DRIVER	OPTION	
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	
<b>DRDH</b>	Housing	<b>N</b> New Construction <b>R</b> Remodel	<b>IC</b> Insulation Contact	<b>4</b> 4" Aperture <b>5</b> 5" Aperture <b>6</b> 6" Aperture <b>6S</b> 6" Shallow	<b>[Blank]</b> Integrated TRIAC/ELV <b>70</b> 0-10V, 750 lm <b>100</b> 0-10V, 1000 lm <b>7C</b> Lutron LDE1, 750 lm <b>10C</b> Lutron LDE1, 1000 lm <b>7W</b> Lutron L3DA3W, 750 lm <b>10W</b> Lutron L3DA3W, 1000 lm	<b>[Blank]</b> None <b>EM</b> Emergency Driver

## LIGHT ENGINE (Product Code Example: DRD3M + 07 + 9 + 27 + SP + WH = DRD3M07927SPWH)

PRODUCT CODE	LUMENS (WATTS)	CRI	CCT	OPTIC	FINISH	DRIVER	
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	
<b>DRD3M</b>	Module	<b>07</b> 750 lm (12.0W) <b>07</b> 1000 lm (14.7W)	<b>9</b> 90+ CRI	<b>27</b> 2700K <b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K	<b>SP</b> Spot <b>FL</b> Flood	<b>WH</b> White <b>BK</b> Black <b>CC</b> Custom Color	<b>[Blank]</b> Integrated TRIAC/ELV <b>A</b> Alternate Dimming

## TRIM (Product Code Example: DRD2T + R + 4 + S + WH = DRD2TR4SWH)

PRODUCT CODE	SHAPE	APERTURE	STYLE	FINISH	
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	
<b>DRD2T</b>	Trim	<b>R</b> Round <b>Q</b> Square on Round	<b>4</b> 4" Aperture <b>5</b> 5" Aperture <b>6</b> 6" Aperture	<b>S</b> Smooth <b>B</b> Baffle	<b>WH</b> White <b>BK</b> Black <b>SW</b> Silver Reflector w/ White Flange <b>CC</b> Custom Color

## Dimensions



**DRD3M**  
Adjustable  
LED Module

