

DCD2

Commercial Recessed LED Downlight

Three optic options to meet the demands of any design

Utilizes deep trims for glare-free lighting



High-lumen, commercial grade downlighting

Powerful, vibrant LED producing up to 4000 lumens

Specs at a Glance

Application	New Construction, Remodel
Housing	4", 6", 8"
Lumen Output (Power)	1500 lm (23.7W), 2000 lm (31.0W), 3000 lm (43.8W), 4000 lm (60.8W)
Color Quality	90+ CRI, 2-step SDCM
CCT Options	2700K, 3000K, 3500K, 4000K
Optics	Narrow Flood (30°), Flood (45°), Wide Flood (60°)
Lifetime (L70)	50,000 hrs
Input Voltage	120/277V
Dimming	Dimming down to 5% for 0-10V, 1% for Lutron® Hi-lume® 1%
Emergency Lighting	Optional Emergency LED Driver for lighting up to 90 minutes in event of power failure
Trim Shape	Round
Trim Style	Smooth
Trim Finish	White, Alzak (low iridescent reflector, white flange), Custom
Listings	cULus Listed, ENERGY STAR® qualified, California Title 24 2016 compliant, UL Listed for Wet Location
Warranty	5 years

Product Selection Guide

FRAME-IN KIT (Product Code Example: **DCDH+N+4+1+15P=DCDHN4115P**)

PRODUCT CODE	APPLICATION	APERTURE	INPUT	DRIVER	OPTION	
DCDH	Housing	N New Construction R Remodel	4 4" Aperture 6 6" Aperture 8 8" Aperture	1 120V 2 277V	15P 0-10V, 1500 lm 20P 0-10V, 2000 lm 30P 0-10V, 3000 lm 40P 0-10V, 4000 lm 15C Lutron LDE1, 1500 lm 20C Lutron LDE1, 2000 lm 30C Lutron LDE1, 3000 lm 15W Lutron L3DA3W, 1500 lm 20W Lutron L3DA3W, 2000 lm 30W Lutron L3DA3W, 3000 lm	[Blank] None EM Emergency Driver <i>Only available for new construction application</i>

MOUNTING (Only applicable for new construction application)

PRODUCT CODE	APPLICATION	APERTURE	INPUT	DRIVER	OPTION
CC	Bar Hanger	LBH Flat Bar Hanger 27"	LBH-24 Flat Bar Hanger 24"	CCA-16 Adjustable C-Channel 11"-18"	
CCA-24	Adjustable C-Channel 17"-26"				

LIGHT ENGINE (Product Code Example: **DCD2M+15+9+27+NF=DCD2M15927NF**)

PRODUCT CODE	LUMENS (WATTS)	CRI	CCT	OPTIC
DCD2M	15 1500 lm (23.7W) 20 2000 lm (31.0W) 30 3000 lm (43.8W) 40 4000 lm (60.8W)	9 90+ CRI	27 2700K 30 3000K 35 3500K 40 4000K	NF Narrow Flood FL Flood WF Wide Flood

TRIM (Product Code Example: **DCD2T+R+4+S+WH=DCD2TR4SWH**)

PRODUCT CODE	SHAPE	APERTURE	STYLE	FINISH
DCD2T	R Round	4 4" Aperture 6 6" Aperture 8 8" Aperture	S Smooth	WH White AZ Low Iridescent Reflector w/ White Flange CC Custom Color

Dimensions



DCD2M
LED Module

