

DRD4

Adjustable LED Downlight

Precise, 360° adjustable downlight expands the capabilities of DMF's award winning OneFrame

Tool-free, field changeable optics and accessories simplify specification and adapt to your design

Class leading 45° tilt and 20°, 30°, or 40° optics put light control at your fingertips

Up to 6000 candelas of focused light with 90+ CRI without sacrificing efficiency



Specs at a Glance

Application	New Construction
Housing	OneFrame Deep Junction Box
Adjustment	360° directional aim, 45° tilt
Lumen Output (Power)	650 lm (9.7W), 800 lm (12.0W)
Color Quality	90+ CRI, 2-step SDCM
CCT Options	2700K, 3000K, 3500K, 4000K
Optics	Spot (20°), Narrow Flood (30°), Flood (40°)
Center Beam Candlepower	6000cd (Spot, 800 lm)
Lifetime (L70)	50,000 hrs
Input Voltage	120/277V
Dimming	Down to less than 5% for TRIAC/ELV at 120V, 1% for 0-10V or Lutron® Hi-Lume® 1% at 120/277V
Emergency Lighting	Optional Emergency LED Driver for lighting up to 90 minutes in event of power failure
Trim Shape	Round
Trim Style	Smooth, Hyperbolic, Pinhole, Beveled Pinhole
Trim Finish	White, Custom
Listings	cULus Listed, ENERGY STAR® qualified, California Title 24 2016 JA8 compliant, UL Listed for Damp Location, DRDHNJD metallic outlet box certified UL514A up to 2 hours fire rating, STC/IIC Sound Rated, IC rated, ASTM E283 certified Air Tight
Warranty	5 years

Product Selection Example

See spec sheets for complete ordering information and options

FRAME-IN KIT (Product Code Example: DRDH + N + JD = DRDHNJD)

PRODUCT CODE	APPLICATION	APERTURE	DRIVER	OPTION
DRDH	Housing	N New Construction	JD Deep Junction Box	[Blank] None
			6O 0-10V, 650 lm	EM EM Driver, Integrated Test Switch
			8O 0-10V, 800 lm	EMS EM Driver, Remote Test Switch
			6C Lutron LDE1, 650 lm	
			8C Lutron LDE1, 800 lm	
			6W Lutron L3DA3W, 650 lm	
			8W Lutron L3DA3W, 800 lm	

LIGHT ENGINE (Product Code Example: DRD4M + 06 + 9 + 27 + SP = DRD4M06927SP)

PRODUCT CODE	LUMENS	CRI	CCT	OPTIC	DRIVER
DRD4M	Module	06 650 lm	9 90+ CRI	27 2700K	SP Spot
		08 800 lm		30 3000K	NF Narrow Flood
			35 3500K	FL Flood	A Alternate Dimming
			40 4000K		

TRIM (Product Code Example: DRD2T + R + JD + S + WH = DRD2TRJDSWH)

PRODUCT CODE	SHAPE	APERTURE	STYLE	FINISH	OPTION
DRD2T	Trim	R Round	JD Deep Junction Box	S Smooth	WH White
			H Hyperbolic	BK Black	[Blank] None
			P Pinhole	SW Silver Reflector w/ White Flange	FL Flangeless
			B Beveled Pinhole	CC Custom Color	EM Test Switch

Dimensions



DRD4M
Adjustable
LED Module

