

DCC4

Adjustable LED Cylinder

Surface, Cord, Stem, Wall Mount

Project:	Type:
Product Code:	Date:



Spec Sheet V-12.01.18



Large, bronze, surface mount shown

- Precise, 360° adjustability expands the capabilities of DMF's DCC Cylinder
- Class leading 45° tilt and 20°, 30°, or 40° optics put light control at your fingertips
- Up to 6000 candelas of focused light with 90+ CRI without sacrificing efficiency
- Tool-free, field changeable optics and accessories simplify specification and adapt to your design



Lumen Output 650 lm (9.7W), 800 lm (12.0W)	Mount Surface, Stem, Cord, Wall, Wall Up/Down	
Color Quality 90+ CRI, 2-step SDCM	Size Length: Small (4"), Medium (8"), Large (12") Diameter: 4"	
Color Temperature  2700K 3000K 3500K 4000K	Finish White, Black, Brushed Aluminum, Bronze, Custom	
Optics  Spot (20°) Narrow Flood (30°) Flood (40°)	Adjustment 360° directional aim, 45° tilt	Dimming TRIAC/ELV 5% 0-10V 1% Lutron Hi-lume® 1%
	Input Voltage 120/277V	
Center Beam Candle Power (CBCP) 6000cd (Spot, 800 lm)	Emergency Lighting Optional Emergency Inverter for lighting up to 90 minutes in event of power failure	

Standards



Ratings



Guarantee

50,000 hrs | 5 years



PRODUCT BUILDER

CYLINDER

PRODUCT CODE		MOUNT & CYLINDER		SIZE		LUMENS		CCT		OPTICS		FINISH		DRIVER	
<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>	
DCC4	Cylinder	SM	Surface Mount	S	Small	06	650 lm	27	2700K	S	Spot	W	White	[Blank]	TRIAC/ELV
		CM	Cord Mount ¹	M	Medium	08	800 lm	30	3000K	N	Narrow Flood	B	Black	O	0-10V ²
		TM	Stem Mount ¹	L	Large	66	650 lm up/down ³	35	3500K	F	Flood	Z	Bronze	C	Lutron LDE1 ^{2,4}
		WM	Wall Mount ²			88	800 lm up/down ³	40	4000K	X	Spot, Narrow	A	Brushed Aluminum	L	Lutron LTEA2W ^{2,5}
										Y	Spot, Flood	C	Custom Color	TE	TRIAC/ELV, Remote Inverter
										Z	Narrow, Flood			OE	0-10V, Remote Inverter ²
														CE	Lutron LDE1, Remote Inverter ^{2,4}
														LE	Lutron LTEA2W, Remote Inverter ^{2,5}

ACCESSORIES

<input type="text"/>	
DCC2X-CCM	Custom Length Cord Mount (up to 96") ¹
DCC2X-CTM	Custom Length Stem Mount (up to 96") ¹

¹ 24" standard length, 48" no charge alternate length; Use Custom Order Form to specify custom length

² Only available in Medium or Large size

³ Only applicable for Large Wall Mounts

⁴ Lutron LDE1 Dimming refers to Lutron Hi-lume 1% EcoSystem LED driver with Soft-on, Fade-to-Black

⁵ Lutron LTEA2W Dimming refers to Lutron Hi-lume 1% 3-wire LED driver