

Apex Series LED Cylinder

Surface, Cord, Stem, Wall Mount



Project:	Type:
Product Code:	Date:

Spec Sheet V-12.01.18



Large, white, cord mount shown

- Apex Series DCCX delivers vivid, accurate light in the form of a completely customizable cylinder
- Powered by the high-performance DRD2X module for a precise, targeted beam of low glare illumination
- Produces up to 4,000 candelas of focused light, perfect for unfinished and high ceilings
- Range of form factors and options to adapt to all kinds of applications

Lumen Output 600 lm (10.0W), 750 lm (12.5W)	Mount Surface, Stem, Cord, Wall, Wall Up/Down	
Color Quality 90+ CRI, 2-step SDCM	Size Length: Small (4"), Medium (8"), Large (12") Diameter: 4"	
Color Temperature  2700K 3000K 3500K 4000K	Finish White, Black, Brushed Aluminum, Bronze, Custom	
Optics  Spot (20°) Narrow Flood (30°) Flood (40°)	Input Voltage 120/277V	Dimming TRIAC/ELV 5% 0-10V 1% Lutron Hi-lume® 1%
Center Beam Candle Power (CBCP) 4000cd (Spot, 750 lm)	Emergency Lighting Optional Emergency Inverter for lighting up to 90 minutes in event of power failure	

Standards



Ratings



Wet location available

Guarantee

50,000 hrs | 5 years

PRODUCT BUILDER

CYLINDER

PRODUCT CODE		MOUNT & CYLINDER		SIZE		LUMENS		CCT		OPTICS		FINISH		DRIVER	
<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>	
DCCX	Cylinder	SW	Surface Mount, Wet	S	Small	06	600 lm	27	2700K	S	Spot	W	White	[Blank]	TRIAC/ELV
		CM	Cord Mount ¹	M	Medium	07	750 lm	30	3000K	N	Narrow Flood	B	Black	O	0-10V ²
		TM	Stem Mount ¹	L	Large	66	600 lm up/down ³	35	3500K	F	Flood	Z	Bronze	C	Lutron LDE1 ^{2,4}
		TW	Stem Mount, Wet ¹			77	750 lm up/down ³	40	4000K	X	Spot, Narrow	A	Brushed Aluminum	L	Lutron LTEA2W ^{2,5}
		WM	Wall Mount ²							Y	Spot, Flood	C	Custom Color	TE	TRIAC/ELV, Remote Inverter
		WW	Wall Mount, Wet ²							Z	Narrow, Flood			OE	0-10V, Remote Inverter ²
														CE	Lutron LDE1, Remote Inverter ^{2,4}
														LE	Lutron LTEA2W, Remote Inverter ^{2,5}

ACCESSORIES

<input type="text"/>	
DCC2X-CCM	Custom Length Cord Mount (up to 96") ¹
DCC2X-CTM	Custom Length Stem Mount (up to 96") ¹
DCC2X-DFT	Decorative Frosted Trim, Closed Bottom

¹ 24" standard length, 48" no charge alternate length; Use Custom Order Form to specify custom length

² Only available in Medium or Large size

³ Only applicable for Large Wall Mounts

⁴ Lutron LDE1 Dimming refers to Lutron Hi-lume 1% EcoSystem LED driver with Soft-on, Fade-to-Black

⁵ Lutron LTEA2W Dimming refers to Lutron Hi-lume 1% 3-wire LED driver