

# DRD3

## Adjustable Recessed LED Downlight

Perfect for specialized designs  
like sloped ceilings

360° rotation enables precise  
directional aim

Won't cross the ceiling plane,  
even when tilted\*



## Specs at a Glance

|                      |  |
|----------------------|--|
| Application          | New Construction, Remodel, Retrofit  |
| Housing              | 4", 5", 6", 6" Shallow   |
| Adjustment           | 360° directional aim, 40° tilt   |
| Lumen Output (Power) | 750 lm (12.0W), 1000 lm (14.7W)  |
| Color Quality        | 90+ CRI, 2-step SDCM   |
| CCT Options          | 2700K, 3000K, 3500K, 4000K   |
| Optics               | Spot (23°), Flood (42°)  |
| Module Finish        | White, Black, Custom   |
| Lifetime (L70)       | 50,000 hrs   |
| Input Voltage        | 120/277V   |
| Dimming              | Down to less than 5% for TRIAC/ELV at 120V, 1% for 0-10V or Lutron® Hi-Lume® 1% at 120/277V  |
| Emergency Lighting   | Optional Emergency LED Driver for lighting up to 90 minutes in event of power failure  |
| Trim Shape           | Round, Square on Round   |
| Trim Style           | Smooth, Baffle   |
| Trim Finish          | White, Black, Silver (silver reflector, white flange), Custom  |
| Listings             | cULus Listed, ENERGY STAR® qualified, California Title 24 2016 JA8 compliant, UL Listed for Damp Location, IC rated, ASTM E283 certified Air Tight |
| Warranty             | 5 years  |

\* 5" and 6" application only

# Product Selection Example

See spec sheets for complete ordering information and options

## FRAME-IN KIT (Product Code Example: DRDH + N + IC + 4 = DRDHNIC4)

| PRODUCT CODE         | APPLICATION          | IC/NON-IC                                     | APERTURE                     | DRIVER   | OPTION  |   |
|----------------------|----------------------|---|------------------------------|--|---|---|
| <input type="text"/> | <input type="text"/> | <input type="text"/>                          | <input type="text"/>         | <input type="text"/>   | <input type="text"/>  |   |
| <b>DRDH</b>          | Housing              | <b>N</b> New Construction<br><b>R</b> Remodel | <b>IC</b> Insulation Contact | <b>4</b> 4" Aperture<br><b>5</b> 5" Aperture<br><b>6</b> 6" Aperture<br><b>6S</b> 6" Shallow | <b>[Blank]</b> Integrated TRIAC/ELV<br><b>70</b> 0-10V, 750 lm<br><b>100</b> 0-10V, 1000 lm<br><b>7C</b> Lutron LDE1, 750 lm<br><b>10C</b> Lutron LDE1, 1000 lm<br><b>7W</b> Lutron L3DA3W, 750 lm<br><b>10W</b> Lutron L3DA3W, 1000 lm | <b>[Blank]</b> None<br><b>EM</b> Emergency Driver |

## LIGHT ENGINE (Product Code Example: DRD3M + 07 + 9 + 27 + SP + WH = DRD3M07927SPWH)

| PRODUCT CODE         | LUMENS (WATTS)       | CRI   | CCT                  | OPTIC  | FINISH                            | DRIVER   |   |
|----------------------|----------------------|---|----------------------|--|-----------------------------------|--|---|
| <input type="text"/> | <input type="text"/> | <input type="text"/>                                  | <input type="text"/> | <input type="text"/>   | <input type="text"/>              | <input type="text"/>   |   |
| <b>DRD3M</b>         | Module               | <b>07</b> 750 lm (12.0W)<br><b>07</b> 1000 lm (14.7W) | <b>9</b> 90+ CRI     | <b>27</b> 2700K<br><b>30</b> 3000K<br><b>35</b> 3500K<br><b>40</b> 4000K | <b>SP</b> Spot<br><b>FL</b> Flood | <b>WH</b> White<br><b>BK</b> Black<br><b>CC</b> Custom Color | <b>[Blank]</b> Integrated TRIAC/ELV<br><b>A</b> Alternate Dimming |

## TRIM (Product Code Example: DRD2T + R + 4 + S + WH = DRD2TR4SWH)

| PRODUCT CODE         | SHAPE                | APERTURE                                   | STYLE  | FINISH                             |  |
|----------------------|----------------------|--|--|------------------------------------|--|
| <input type="text"/> | <input type="text"/> | <input type="text"/>                       | <input type="text"/>   | <input type="text"/>               |  |
| <b>DRD2T</b>         | Trim                 | <b>R</b> Round<br><b>Q</b> Square on Round | <b>4</b> 4" Aperture<br><b>5</b> 5" Aperture<br><b>6</b> 6" Aperture | <b>S</b> Smooth<br><b>B</b> Baffle | <b>WH</b> White<br><b>BK</b> Black<br><b>SW</b> Silver Reflector w/ White Flange<br><b>CC</b> Custom Color |

## Dimensions



**DRD3M**  
Adjustable  
LED Module

