

DCP9

LED Pendant

Cord, Stem Mount

Project:	Type:
Product Code:	Date:

Spec Sheet V-08.15.19



- Versatile LED pendant supports the lighting needs of standard open and high ceilings alike
- Produces up to 9,000 lm of commercial high-lumen illumination
- Die-cast aluminum with no visible hardware for a sleek, completely symmetrical design
- Precision-injected, frosted prismatic shade
- Customizable with multiple mounting and finish options

Lumen Output 1500 lm (15W), 2000 lm (23W), 3000 lm (32W), 4000 lm (43W), 5000 lm (55W), 9,000 lm (107W)		Mount Stem, Cord
Color Quality 90+ CRI, 2-step SDCM		Cord/Stem Length Cord: 96"; Stem: 24" (standard) up to 96" (custom)
Color Temperature   3500K 4000K		Pendant Finish White, Black, Brushed Aluminum
Input Voltage 120/277V		Shade Diameter 16"
Dimming 0-10V, Lutron Hi-lume®		Shade Finish Frosted

Emergency Lighting

Optional Emergency LED Driver for lighting up to 90 minutes in event of power failure

Standards



Guarantee

50,000 hrs | 5 years

**PRODUCT BUILDER****LED PENDANT**

PRODUCT CODE		MOUNT		LUMENS		CCT		FINISH		DRIVER	
<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>	
DCP9	Pendant	CM	Cord Mount ^{1,2}	01	1500 lm	35	3500K	WH	White	O	0-10V
		TM	Stem Mount ¹	02	2000 lm	40	4000K	BK	Black	C	Lutron LDE1 ⁴
				03	3000 lm			BA	Brushed Aluminum	L	Lutron LTEA2W ⁵
				04	4000 lm					OE	0-10V, Emergency Driver
				05	5000 lm ³					CE	Lutron LDE1, Emergency Driver ⁴
				09	9,000 lm ³					LE	Lutron LTEA2W, Emergency Driver ⁵

SHADE

PRODUCT CODE		SHAPE		DIAMETER		STYLE		FINISH	
<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>	
DCPS	Shade	R	Round	16	16" Diameter	P	Prismatic	FR	Frosted

¹ Cord: 96" length; Stem: 24" length (standard), up to 96" (custom)² White cord standard for White finish, black cord standard for Black finish, silver cord standard for Brushed Aluminum finish; unless specified otherwise³ Only compatible with 0-10V driver⁴ Lutron LDE1 Dimming refers to Lutron Hi-lume 1% EcoSystem LED driver with Soft-on, Fade-to-Black⁵ Lutron LTEA2W Dimming refers to Lutron Hi-lume 1% 2-wire LED driver, 120V only