

DCC2

LED Cylinder

Surface, Cord, Stem, Wall Mount

Project:	Type:
Product Code:	Date:

Spec Sheet V-12.01.19



Large, white, surface mount shown

- The DCC2 cylinder's combination of precise illumination and refined aesthetics can take your designs to new heights
- Available in a range of form factors, mounting options, and color finishes, the DCC2 can be configured exactly the way you want it
- Constructed from die-cast aluminum with no visible hardware for a sleek, completely symmetrical design

Lumen Output 750 lm (10.8W), 1000 lm (12.8W), 1500 lm (19.5W), 2000 lm (29.0W)	Mount Surface, Stem, Cord, Wall, Wall Up/Down	
Color Quality 90+ CRI, 2-step SDCM	Size Length: Small (4"), Medium (8"), Large (12") Diameter: 4"	
Color Temperature 2700K 3000K 3500K 4000K	Finish White, Black, Brushed Aluminum, Bronze, Custom	Stem/Cord Length 24" (standard), Up to 96" (custom)
Light Distribution General	Input Voltage 120/277V	Dimming TRIAC/ELV 5% 0-10V 1% Lutron Hi-lume® 1%

Emergency Lighting

Optional Remote Inverter or Emergency LED Driver for lighting up to 90 minutes in event of power failure

Standards 	Ratings Wet location available	Guarantee 50,000 hrs 5 years
----------------------	--	--



PRODUCT BUILDER

CYLINDER

PRODUCT CODE		MOUNT & CYLINDER		SIZE		LUMENS		CCT		FINISH		DRIVER	
DCC2	Cylinder	SW	Surface Mount, Wet	S	Small	07	750 lm	27	2700K	WH	White	[Blank]	TRIAC/ELV
		CM	Cord Mount ^{1,2}	M	Medium	10	1000 lm	30	3000K	BK	Black	O	0-10V ³
		TM	Stem Mount ¹	L	Large	15	1500 lm ⁴	35	3500K	BZ	Bronze	C	Lutron LDE1 ^{3,6}
		TW	Stem Mount, Wet ¹			20	2000 lm ⁴	40	4000K	BA	Brushed Aluminum	L	Lutron LTEA2W ^{3,7}
		WM	Wall Mount ³			77	750 lm up/down ⁵			CC	Custom Color	TE	TRIAC/ELV, Remote Inverter
		WW	Wall Mount, Wet ³			11	1000 lm up/down ⁵					OE	0-10V, EM Driver ³
						71	750/1000 lm up/down ⁵					CE	Lutron LDE1, EM Driver ^{3,6}
												LE	Lutron LTEA2W, EM Driver ^{3,7}

ACCESSORIES

DCC2X-CCM	Custom Length Cord Mount (up to 96") ¹
DCC2X-CTM	Custom Length Stem Mount (up to 96") ¹
DCC2X-48CM	48" Alternate Length Cord Mount ¹
DCC2X-DFT	Decorative Frosted Trim

¹ 24" standard length, 48" no charge alternate length (cord); Use Custom Order Form to specify custom length

² White cord standard for White finish, black cord standard for Black or Bronze finish, silver cord standard for Brushed Aluminum finish; unless specified otherwise

³ Only available in Medium or Large size

⁴ Only available in Large size, 0-10V or Lutron driver

⁵ Only applicable for Large Wall Mounts

⁶ Lutron LDE1 Dimming refers to Lutron Hi-lume 1% EcoSystem LED driver with Soft-on, Fade-to-Black

⁷ Lutron LTEA2W Dimming refers to Lutron Hi-lume 1% 2-wire LED driver, 120V only