



Politan Row Food Hall in Atlanta, GA
Lighting Design by Rachel Levy Designs

CONTENTS

Overview

DRD Series	4
DCD Series	12
DCC Cylinders	16
H Series	20
DRD5S Series	24
Technology	26

Product Details

DRD2 Fixed Downlight System	29
DRD4 Adjustable Downlight System	37
DCD3 Higher-Lumen Fixed Downlight	42
DCD4 Higher-Lumen Adjustable Downlight	44
DCC Cylinder	46
H Series Residential Lighting	48
DRD5S Surface Mounts	50

Downlight Comparison	54
----------------------	----

DRD Series



Modular Downlighting System

DMF's upgraded modular downlighting system, powered by the next generation DRD Series, is now more versatile than ever – fixed, adjustable or wall wash, round or square, 750 to 1500 lumens. Featuring proprietary integrated TRIAC/ELV and 0-10V drivers for optimal performance and reliability, the DRD Series can keep up with the fast-paced and ever-changing nature of your projects and can be the solution you go to every day.

The DRD Series can support 98% of recessed lighting use cases.



DRD Series Featuring
Flangeless Wood Installation



DRD2
Fixed Downlight

The next generation of high-performance LED downlighting is here. Our engineers redesigned the DRD2 to be more versatile than ever, adding field-changeable optics, 1% dimming with any control system, and plug and play 0-10V wiring. It's simplicity engineered.




DRD4
Adjustable Downlight

The adjustable DRD4 with class-leading 45° tilt provides ultimate flexibility in directional lighting in a compact, modular downlight. With an integrated driver, multiple beam options, and field-changeable accessories, it delivers tool-free aimed and lockable lighting that adapts to the demands of today's designs.



M Series






With the all-new M Series, the DRD Series is now more versatile than ever.



M Series

4" Round & Square Housing

The all-new M Series is designed to adapt. Building on our award-winning OneFrame platform, the M Series offers even more housing rating options, including Standard, Fire-Rated, and Chicago Plenum, along with specialty options such as Low-Profile and Double Housing. The compact, 4" housing installs easily and precisely for optimal fixture placement in crowded plenum space, to accommodate ductwork, framing, and plumbing.

-  *Insulation Contact (IC) Rated*
-  *ASTM E283 Certified Air Tight*
-  *STC/IIC Sound Rated*
-  *Chicago Plenum*
-  *Code compliant for use in appropriate fire-rated assemblies for up to 2-hours*



Round on Square
Unobstructed illumination from a square profile.



Pinhole
Accentuates light distribution for a narrow, spotlight effect. Choose between straight or beveled edges and round or square shape.



Hyperbolic
A unique reflector that provides completely smooth, uniform light and blends into ceilings.



Flangeless
Flangeless wood application or use with low-profile mud flange. Available for Round, Square, Hyperbolic, Pinhole, and Wall Wash trims.

A Perfect Match

The materials, heft, and finish of our M Series trims set them apart. The precision-crafted aluminum trims meet the design aesthetic of any project – wall wash, pinhole, round, square, flangeless – all completely interchangeable and available in five standard finishes and a custom color option.



Round
Featuring a classic and elegant design, the Round Trim pairs perfectly with any project.



Square
A modern look that's expertly die cast with sharp edges and precise corners.



Decorative
Finely crafted acrylic that delivers a subtle, radiant glow. Options include an open or closed bottom, frosted or clear finish, and round or square shape.



Wall Wash
Perfect for delivering broad, consistent light across a wall surface with an unobtrusive round or square design that stays above the ceiling plane.

DCD Series



Higher-Lumen Downlighting System

The DCD Series is a higher-lumen, interoperable downlighting solution that radically simplifies configuration in the field. With just one housing type, you can change beam angles, increase light output, service the driver, and even switch to an adjustable. All without tools.

Performance.
Flexibility. And your
job, made simpler.




DCD3
Higher-Lumen Fixed Downlight

The DCD3 delivers up to 3000 lumens of superior lighting at 90+ CRI, perfect for higher ceiling applications. Its tool-free, field-changeable optics and trims offer endless lighting customization, allowing you to easily change how your spaces feel and perform with minimal labor. Whether you're lighting a concert hall or a corridor, the DCD3 gives you impressive versatility that's incredibly simple to use.

DCD4
Higher-Lumen Adjustable Downlight


The DCD4 puts powerful lighting exactly where you want it with 360° of aimable rotation and up to 40° of tilt. Simply unlock a lever and knob to allow precise, infinite adjustments and then lock it back into place. The process is quick, simple, and 100% tool-free. And with field-changeable beam angles and lumen outputs, you can further customize your lighting, even after installation.






DCD Frame

The foundation for the DCD Series, the DCD Frame offers easy installation with a quick connector and flexibility at every stage. After installation, you can decide to install fixed or adjustable downlights and even switch to accents, wall washes, or change beam angles.




DCD3 Trim Standard Round Beveled, Warm Diffuse




DCD4 Trim Standard Round Beveled



DCD3 Trim Flangeless Pinhole



DCD4 Trim Flangeless Pinhole



DCD3 Trim Standard Round Beveled, Clear Diffuse



DCD4 Trim Flangeless Pinhole



DCC Cylinders



Modern Cylinder System

By combining a suite of customizable features with our highest performing LED modules yet, the DCC provides brilliant illumination and a beautiful design versatile enough for whatever your project needs.

Mix and match to
create the light you
need for the space
you want.



DCC CYLINDERS



Customization
Unmatched in
the Industry



Options & Accessories

Shades, trims, specialty options, even the light engine can all be swapped out in the field, giving you control during and after the installation.



Uplight
Enables light output at elevated levels, while providing glare-free ambiance and the ability to highlight architectural elements.



Snoot
Channels light source and decreases visual cutoff angle to increase focus and mitigate glare.



Hyperbolic Trim
Smoothly transitions from surface to source for smooth, uniform light.



Decorative Trim
Finely crafted acrylic subtly fills your space with beautiful ambient light.



Round & Flat Shades
Re-imagined for more diverse environments while creating a more focused and comfortable general light.




Junction Box Cover
Completes the cylinder's look in open ceiling applications.



Wet Location Rated
Available moisture protection options are IP65 and UL Listed as water-resistant and rated for outdoor use.

H Series



DMF Performance at an Attainable Price

The H Series is an all-new modular downlight system that brings the best of our award-winning design to the whole home. With several trim options and high-quality finishes, the H Series is simple to select, order, install, and maintain for any new construction or remodel project.

Now, brilliant illumination and reliable performance are available in any space, for nearly any budget.

One Versatile Module

Up to 950 lumens of 90+ CRI delivers brilliant, accurate, and comfortable light that enhances any design finish and experience. Optimized to provide exceptional performance with any smart home or connected dimmer.



Brilliant Illumination

The Integrated Natural Warm Dim seamlessly transitions from comfortable white to warm light without losing color accuracy and the Brightness Switch enables field selectable light output, including ambient, standard, and higher ceiling environments.

Flexible Housing Applications

Strong, lightweight, and stackable to consolidated shelf space, the H Series Housings are designed to simplify installations. The housings feature bar hangers, wood joist mounting screws, or pop out springs to ensure a quick and accurate installation. Made from sustainable materials, the housings are recyclable and 100% manufactured in the USA.



Contemporary Trims

With a clean and modern design, the H Series Trims complement any space. Available in Round, Flush, Square, or Adjustable, and in 4" or 3" apertures, they feature die-cast aluminum construction and metal clips to provide a strong, gap-free hold and easy tool-free installation.



Round, 4" & 3"

Versatile solution that complements any design, reduces glare.



Flush, 4" & 3"

Best for showers and closets, produces uniform light.



Square, 4" & 3"

Modern home aesthetic, creates clean lines.



Adjustable, 4" & 3"

Great for sloped ceilings, and highlighting art or architecture.




DRD5S Series

Surface Mount Downlighting

The DRD5S redefines what's possible for a surface mount downlight. Packed with technical breakthroughs, the ultra-thin DRD5S matches the elegance of a recessed downlight. In addition, it's more versatile because it can fit more applications, even those with limited plenum space.


See the light,
not the fixture.



DRD5S

4" Surface Mount

The DRD5S's minimal design is available in multiple form factors, with the 4" Round and Square matching the appearance of recessed lights. These models also include optional Integrated EM Test Switch and Non-Conductive Dead Front variants.



DRD5S

8" Round Surface Mount

This minimalist downlight takes everything that makes the original DRD5S exceptional, and expands on it. This area light can fill a room with inviting, accurate illumination. In addition, its SurfaceFrame compatibility simplifies installation and makes it totally interoperable with the rest of the DRD5S family.



DRD5S


18" Linear Surface Mount

A fresh take on the DRD5S, this linear area light delivers 1500 lumens of 90+ CRI light in a unique form factor. Like our other downlights in this series, the linear version features a proprietary integrated driver and small footprint, making it a great choice for new construction or retrofit applications.



Integrated Driver

Technology



Next Generation Dimming

Designed and developed in-house to ensure optimal performance, our drivers provide 1% flicker-free dimming, smooth fading, and compatibility with 0-10V or forward or reverse phase dimmers. Fully integrated into the modules, we've tested and finely tuned our drivers to be compatible with a broad range of dimmers from various manufacturers. This high-performance solution in a compact form factor simplifies design, installation, and maintenance.

Industry leading performance and guaranteed dimming compatibility.

Warm Dim

Technology



Comfort Without Compromise

DMF's Warm Dim technology transforms how your spaces look and feel without sacrificing simplicity or performance. Warm Dim transitions from a bright and inviting 3000K to as low as 1800K, for a warm and intimate environment, maintaining a consistent CRI value and ENERGY STAR® rating throughout.

KEY FEATURES

- Maintains consistent CRI value throughout the dimming range
- Powered by one premium chip that utilizes color mixing phosphors to produce a warm, relaxing glow
- Thoughtfully engineered to create the right light for each situation
- Part of the modular, unified DMF downlighting system that gives you the flexibility to light an entire project

DRD2

Fixed Downlight System



- Produces up to 1500 lumens of 93+ CRI lighting for natural, true-to-life colors without sacrificing stellar efficiency
- Field-changeable light distribution ranging from 15° to 90°+
- Smooth, flicker-free dimming down to 1% with centralized or local control
- Integrated driver, plug-and-play connection, and Twist & Lock trims
- Flexibility during and after installation with interchangeable modules, optics and trims

Application New Construction, Remodel, Retrofit		Compatible Housings/Fixtures M Series; SurfaceFrame; Classic Frame: 4", 5", 6", Cylinder	
Input Voltage 120/277V	Color Quality 93+ CRI, 2-step SDCM	Delivered Lumens 750 lm (9.5W), 1000 lm (12.5W), 1250 lm (14.3W), 1500 lm (17.5W)	
1% Dimming TRIAC/ELV, 0-10V, EcoSystem		Beam Spread <div><div><div>15° Narrow Spot</div><div>25° Spot</div><div>40° Flood</div><div>60° Wide Flood</div><div>90°+ General Ambient</div><div>40° x 20° Linear Spread</div><div>Soft Focus</div></div></div>	
Color Temperatures <div><div>2700K</div><div>3000K</div><div>3500K</div><div>4000K</div><div>Warm Dim, 3000–1800K</div></div>			

Emergency Lighting
Optional Emergency LED Driver with integrated or remote EM Test Switch for lighting up to 90 minutes in event of power failure

Standards <div><div>JA8</div><div>ENERGY STAR</div><div>CERTIFIED US-CA</div><div>Declare.</div></div>		Ratings <div><div>Wet Location</div></div>	Guarantee <div><div>50k HOURS</div><div>5 YEARS</div></div>
---	--	---	--


PRODUCT CODE

PRODUCT		LUMENS		CRI		CCT		BEAM SPREAD		DIMMING	
DRD2M	Module	07	750 lm	9	93+ CRI	27	2700K	GA	General Ambient (90°)	T	Integrated TRIAC/ELV
		10	1000 lm			30	3000K	NS	Narrow Spot (15°) ²	O	Integrated 0-10V
		12	1250 lm			35	3500K	SP	Spot (25°)	A	Alternate - for use with EM or Lutron EcoSystem ³
		15	1500 lm			40	4000K	FL	Flood (40°)		
						3W	Warm Dim ¹	WF	Wide Flood (60°)		
								LS	Linear Spread (40° x 20°)		
								SF	Soft Focus		


¹ Only available in 1000 lm
² Not available in Warm Dim CCT
³ Lutron EcoSystem refers to Lutron LDE1 driver

M Series 4" Round


HOUSINGS



M4NCRS
New Construction
Standard




M4NCRF
New Construction
Fire Rated




M4DHRS
Double
Housing




M4CPRS
Chicago
Plenum




M4LTRS
Low Profile
Standard



M4LTRF
Low Profile
Fire Rated



M4NCRS7OEM
Emergency
Standard



M4NCRF7OEM
Emergency
Fire Rated



M4RMRS
Remodel
Standard



M4RMRF
Remodel
Fire Rated



M4CC
Concrete
Construction

M Series 4" Round

TRIMS



M4TRSWH
Round



M4TRCWH
Square Conversion



M4TRHWH
Hyperbolic



M4TRPWH
Pinhole



M4TRBWH
Beveled Pinhole



M4TRLWH
Wall Wash



M4TRSWHDOF
Decorative: Open,
Frosted



M4TRSWHDCF
Decorative: Closed,
Frosted



M4TRSWHDCC
Decorative: Closed,
Clear, Frosted Side



M4TRSWHDCCF
Decorative: Closed,
Clear, Frosted Inside



M4TRSWHEM
Emergency



M4TRSWHDF
Non-Conductive
Dead Front



M4TRSWHFL*
Round Flangeless



M4TRHWHFL*
Hyperbolic Flangeless



M4TRPWHFL*
Pinhole Flangeless



M4TRBWHFL*
Beveled Pinhole
Flangeless



M4TRLWHFL*
Wall Wash Flangeless



M4XRMUD
Flangeless Mud Plate



M4KRTEMPLATE
Flangeless Wood
Template


*Flangeless Mud Plate required for drywall ceiling installation;
Flangeless Wood Template recommended for wood ceiling installation

FINISH OPTIONS


- White (WH)
- Black (BK)
- Bronze (BZ)
- Clear Diffuse, White Flange (CW)
- Warm Diffuse, White Flange (WW)
- Custom Color (CC)

M Series 4" Square


HOUSINGS




M4NCSS
New Construction
Standard




M4NCSF
New Construction
Fire Rated




M4CPSS
Chicago
Plenum




M4LTSS
Low Profile
Standard



M4LTSF
Low Profile
Fire Rated



M4NCSS7OEM
Emergency
Standard



M4NCSF7OEM
Emergency
Fire Rated


















M4RMSS
Remodel
Standard



M4RMSF
Remodel
Fire Rated

M Series 4" Square

TRIMS

 <div>M4TSSWH Square</div> <div><div></div><div></div><div></div><div></div><div></div><div></div></div>	 <div>M4TSQWH Round on Square</div> <div><div></div><div></div><div></div><div></div><div></div><div></div></div>	 <div>MRTSPWH Pinhole</div> <div><div></div><div></div><div></div><div></div><div></div><div></div></div>	 <div>M4TSBWH Beveled Pinhole</div> <div><div></div><div></div><div></div><div></div><div></div><div></div></div>	 <div>M4TSSWWH Wall Wash</div> <div><div></div><div></div><div></div><div></div><div></div><div></div></div>
 <div>M4TSSWHDCF Decorative: Closed, Frosted</div> <div><div></div><div></div></div>	 <div>M4TSSWHDCCF Decorative: Closed, Clear, Frosted Inside</div> <div><div></div><div></div></div>	 <div>M4TSSWHEM Emergency</div> <div><div></div><div></div><div></div></div>	 <div>M4TSSWHFL* Square Flangeless</div> <div><div></div><div></div><div></div><div></div></div>	 <div>M4TSQWHFL* Round on Square Flangeless</div> <div><div></div><div></div><div></div><div></div></div>
 <div>M4TSPWHFL* Pinhole Flangeless</div> <div><div></div><div></div><div></div><div></div></div>	 <div>M4TSBWHFL* Beveled Pinhole Flangeless</div> <div><div></div><div></div><div></div><div></div></div>	 <div>M4TSSWWHFL* Wall Wash Flangeless</div> <div><div></div><div></div><div></div><div></div></div>	 <div>M4XSMUD Flangeless Mud Plate</div>	 <div>M4KSTEMPLATE Flangeless Wood Template</div>

*Flangeless Mud Plate required for drywall ceiling installation


FINISH OPTIONS

- White (WH)
- Black (BK)
- Bronze (BZ)
- Clear Diffuse, White Flange (CW)
- Warm Diffuse, White Flange (WW)
- Custom Color (CC)


SurfaceFrame

Shallow Junction Box


SURFACEFRAME HOUSINGS & TRIMS



DRDHNJO
New Construction
Fire Rated



DRDHNJO7OEMS
Emergency
Fire Rated



DRD2TRJSWH
Surface Mount

Classic Frames

4" HOUSINGS & TRIMS



DRDHNIC4
4" New Construction




DRDHRIC4
4" Remodel




DRDHNIC4S
4" Shallow New Construction



DRDHRIC4S
4" Shallow Remodel



DRD2TR4SWH
4" Smooth



DRD2TR4BWH
4" Baffle

6" HOUSINGS & TRIMS



DRDHRIC6S
6" Remodel




DRD2TR6SWH
6" Smooth




DRD2TR6BWH
6" Baffle

Retrofit

4" TRIMS



DRD2TR4SWH
4" Smooth



DRD2TR4BWH
4" Baffle

5" TRIMS




DRD2TR5SWH
5" Smooth




DRD2TR5BWH
5" Baffle

6" TRIMS



DRD2TR6SWH
6" Smooth



DRD2TR6BWH
6" Baffle

DRD2 OPTICS ACCESSORIES

DRD2X-GA	Conversion Kit: DRD2 Module to General Ambient (90°+)
DRD2X-NS	Narrow Spot (15°)
DRD2X-SP	Spot (25°)
DRD2X-FL	Flood (40°)
DRD2X-WF	Wide Flood (60°)
DRD2X-LS	Linear Spread (40° x 20°)
DRD2X-SF	Soft Focus
DRD2X-OP	Optics Kit: NS, S, F, WF, LS, SF

COMPATIBLE HOUSINGS & TRIMS

ADAPTERS



DRD2X-QCM-ED
Edison Adapter



DRD2X-QCM-GU
GU-24 Adapter



DRD2X-QCM-M
Male IDEAL PowerPlug® Adapter



DRD2X-QCM-HW
Hardwire Adapter

FINISH OPTIONS

- ☐ White (**WH**)
- ☒ Black (**BK**)




















DRD4

Adjustable Downlight System



- 360° directional aiming for complete light coverage
- Class leading 45° tilt with 15°, 25° or 40° field-changeable light distributions
- Smooth, flicker-free dimming down to 1% with centralized or local control
- Integrated driver, plug-and-play connection, and Twist & Lock trims
- Flexibility during and after installation with interchangeable modules, optics and trims

Application New Construction, Remodel, Retrofit		Compatible Housings/Fixtures M Series; Classic Frame: 4", 5", 6", Cylinder	
Delivered Lumens 750 lm (9.7W), 1000 lm (12W)		Adjustment 360° Directional Aim, 45° Tilt	
1% Dimming TRIAC/ELV, 0-10V, EcoSystem		Input Voltage 120/277V	Color Quality 93+ CRI, 2-step SDCM
Color Temperatures <div><div> 2700K</div><div> 3000K</div><div> 3500K</div><div> 4000K</div><div> Warm Dim, 3000–1800K</div></div>		Beam Spread <div><div> 15° Narrow Spot</div><div> 25° Spot</div><div> 40° Flood</div><div> 60° x 30° Linear Spread</div><div> Soft Focus</div></div>	
Emergency Lighting Optional Emergency LED Driver with integrated or remote EM Test Switch for lighting up to 90 minutes in event of power failure			
Standards <div><div></div><div></div><div></div><div></div></div>		Ratings <div><div> Damp Location</div></div>	Guarantee <div><div></div><div></div></div>


PRODUCT CODE

PRODUCT CODE		LUMENS		CRI		CCT		BEAM SPREAD		FINISH		DIMMING	
DRD4M	Module	07	750 lm	9	93+ CRI	27	2700K	NS	Narrow Spot (15°)	[Blank]	Black	T	Integrated TRIAC/ELV
		10	1000 lm			30	3000K	SP	Spot (25°)	W	White	O	Integrated 0-10V
						35	3500K	FL	Flood (40°)			A	Alternate - for use with EM or Lutron EcoSystem ²
						40	4000K	LS	Linear Spread (60° x 30°)				
						3W	Warm Dim ¹	SF	Soft Focus				


¹ Only available in 1000 lm
² Lutron EcoSystem refers to Lutron LDE1 driver

M Series 4" Round


HOUSINGS



M4NCRS
New Construction
Standard




M4NCRF
New Construction
Fire Rated




M4DHRS
Double
Housing




M4CPRS
Chicago
Plenum




M4LTRS
Low Profile
Standard



M4LTRF
Low Profile
Fire Rated



M4NCRS7OEM
Emergency
Standard



M4NCRF7OEM
Emergency
Fire Rated



M4RMRS
Remodel
Standard



M4RMRF
Remodel
Fire Rated



M4CC
Concrete
Construction

M Series 4" Round

TRIMS



M4TRSWH
Round



M4TRHWH
Hyperbolic



M4TRPWH
Pinhole



M4TRBWH
Beveled Pinhole



M4TRSWHEM
Emergency



M4TRSWHFL*
Round Flangeless



M4TRHWHFL*
Hyperbolic Flangeless




M4TRPWHFL*
Pinhole Flangeless



M4TRBWHFL*
Beveled Pinhole
Flangeless



M4XRMUD
Flangeless Mud Plate



M4KRTEMPLATE
Flangeless Wood
Template


*Flangeless Mud Plate required for drywall ceiling installation;
Flangeless Wood Template recommended for wood ceiling installation

FINISH OPTIONS

- White (WH)
- Black (BK)
- Bronze (BZ)
- Clear Diffuse, White Flange (CW)
- Warm Diffuse, White Flange (WW)
- Custom Color (CC)

M Series 4" Square

HOUSINGS & TRIMS




M4NCSS
New Construction
Standard




M4NCSF
New Construction
Fire Rated



M4CPSS
Chicago
Plenum



M4RMSS
Remodel
Standard



M4RMSF
Remodel
Fire Rated



M4LTSS
Low Profile
Standard




M4LTSF
Low Profile
Fire Rated



M4NCSS7OEM
Emergency
Standard




M4NCSF7OEM
Emergency
Fire Rated




M4TSQWH
Round on Square

○ ● ● ● ●




MRTSPWH
Pinhole

○ ● ● ● ●




M4TSBWH
Beveled Pinhole

○ ● ● ● ●




M4TSQWHFL*
Round on Square
Flangeless

○ ●




MRTSPWHFL*
Pinhole Flangeless

○ ● ● ● ●




M4TSBWHFL*
Beveled Pinhole
Flangeless

○ ● ● ● ●



M4XSMUD
Flangeless Mud Plate



M4KSTEMPLATE
Flangeless Wood
Template

FINISH OPTIONS

○ White (WH)

● Black (BK)

● Bronze (BZ)

○ Clear Diffuse, White Flange (CW)

● Warm Diffuse, White Flange (WW)

● Custom Color (CC)

*Flangeless Mud Plate required for drywall ceiling installation

Classic Frames

4" HOUSINGS & TRIMS



DRDHNIC4
4" New Construction



DRDHRIC4
4" Remodel



DRDHNIC4S
4" Low Profile New Construction



DRDHRIC4S
4" Low Profile Remodel



DRD2TR4SWH
4" Smooth


○ ●




DRD2TR4BWH
4" Baffle

○

6" HOUSINGS & TRIMS




DRDHRIC6S
6" Remodel



DRD2TR6SWH
6" Smooth

○ ●




DRD2TR6BWH
6" Baffle

○


Retrofit

4" TRIMS



DRD2TR4SWH
4" Smooth

○ ●



DRD2TR4BWH
4" Baffle

○

5" TRIMS



DRD2TR5SWH
5" Smooth


○ ●



DRD2TR5BWH
5" Baffle


○

6" TRIMS



DRD2TR6SWH
6" Smooth

○ ●



DRD2TR6BWH
6" Baffle

○

ADAPTERS



DRD2X-QCM-ED
Edison Adapter



DRD2X-QCM-GU
GU-24 Adapter



DRD2X-QCM-M
Male IDEAL
PowerPlug® Adapter



DRD2X-QCM-HW
Hardwire Adapter

DCD3

Higher-Lumen Fixed Downlight



- Radically simplifies configuration in the field
- Efficiently produces up to 3000 lumens of superior lighting at 90+ CRI
- Wide range of interoperable lighting options including lumen, color temperature, and beam angle
- Integrated Twist & Lock driver for easy maintenance
- Connect the power and driver with a simple snap, no tools required

Application New Construction, Remodel	Compatible Housings DCD Frame	Aperture 4" Commercial
Delivered Lumens 1500 lm (20W), 2000 lm (28W), 2500 lm (37W), 3000 lm (40W)	Input Voltage 120/277V	1% Dimming 0-10V, Lutron EcoSystem
Color Quality 90+ CRI, 2-step SDCM	Beam Spread <div><div>15° Narrow Spot</div><div>25° Spot</div><div>40° Flood</div><div>60° Wide Flood</div></div>	
Color Temperatures <div><div>2700K</div><div>3000K</div><div>3500K</div><div>4000K</div></div>		

Emergency Lighting
Optional Emergency LED Driver for lighting up to 90 minutes in event of power failure

Standards <div><div>ENERGY STAR</div><div>UL CERTIFIED US-CA</div><div>Declare.</div></div>	Ratings <div><div>Wet Location</div></div>	Guarantee <div><div>50k HOURS</div><div>5 YEARS</div></div>
--	---	--

PRODUCT CODE

PRODUCT		LUMENS		CRI		CCT		OPTICS		DRIVER	
DCD3M	Module	15	1500 lm	9	90+ CRI	27	2700K	NS	Narrow Spot	[Blank]	Integrated 0-10V
		20	2000 lm			30	3000K	SP	Spot	A	Alternate - for use with EM or Lutron EcoSystem¹
		25	2500 lm			35	3500K	FL	Flood		
		30	3000 lm			40	4000K	WF	Wide Flood		

¹ Lutron EcoSystem refers to Lutron LDE1 driver

DCD3

Higher-Lumen Fixed Downlight

COMPATIBLE HOUSINGS & TRIMS

DCD Frame

DCD FRAME HOUSINGS & TRIMS



DCDHNR4
New Construction



DCDHNR415OEM
New Construction
Emergency



DCDHRR4
Remodel

DCD3TR4SWH
Round Beveled

DCD3TR4HWH
Hyperbolic

DCD3TR4PWH
Pinhole

DCD3TR4LWH
Low Profile

DCD3TR4WWH
Wall Wash

DCD3TR4SWHEM
Emergency

DCD3TR4SWHDOF
Decorative: Open,
Frosted

DCD3TR4SWHFL*
Round Flangeless

DCD3TR4HWHFL*
Hyperbolic Flangeless

DCD3TR4PWHFL*
Pinhole Flangeless

DCD3TR4WWHFL*
Wall Wash Flangeless

DCDHX-MUD-FL
Flangeless Mud Plate

*Requires Flangeless Mud Plate

- FINISH OPTIONS
- White (WH)
 - Black (BK)
 - Clear Diffuse (CD)
 - Warm Diffuse (WD)
 - Black, White Flange (BW)
 - Clear Diffuse, White Flange (CW)
 - Warm Diffuse, White Flange (WW)
 - Custom Color (CC)

DCD4

Higher-Lumen Adjustable Downlight




- Radically simplifies configuration in the field
- 360° rotation and 40° tilt for precise, aimable lighting
- Wide range of interoperable lighting options including lumen, color temperature, and beam angle
- Integrated Twist & Lock driver for easy maintenance
- Connect the power and driver with a simple snap, no tools required

Application New Construction, Remodel	Compatible Housings DCD Frame	Aperture 4" Commercial
Delivered Lumens 1500 lm (21W), 2000 lm (37W), 2500 lm (40W)	Input Voltage 120/277V	1% Dimming 0-10V, Lutron EcoSystem
Color Quality 90+ CRI, 2-step SDCM	Adjustment 360° directional aim, 40° tilt	
Color Temperatures <div><div><div>2700K</div><div>3000K</div><div>3500K</div><div>4000K</div></div></div>	Beam Spread <div><div><div>15° Narrow Spot</div><div>25° Spot</div></div><div><div>40° Flood</div><div>60° Wide Flood</div></div></div>	
Specialty Lens Option <div><div>Linear Spread</div></div>		

Standards



Ratings



Guarantee



PRODUCT CODE

PRODUCT		LUMENS		CRI		CCT		OPTICS		DRIVER	
DCD4M	Module	15	1500 lm	9	90+ CRI	27	2700K	NS	Narrow Spot	[Blank]	Integrated 0-10V
		20	2000 lm			30	3000K	SP	Spot	A	Alternate - for use with EM or Lutron EcoSystem ¹
		25	2500 lm			35	3500K	FL	Flood		
						40	4000K	WF	Wide Flood		
								LS	Linear Spread		

¹ Lutron EcoSystem refers to Lutron LDE1 driver

DCD4

Higher-Lumen Adjustable Downlight

COMPATIBLE HOUSINGS & TRIMS

DCD Frame

DCD FRAME HOUSINGS & TRIMS




DCDHNR4
New Construction



DCDHNR415OEMS
New Construction
Emergency



DCDHRR4
Remodel



DCD4TR4SWH
Round Beveled



DCD4TR4PWH
Pinhole



DCD4TR4SWHFL*
Round Flangeless



DCD4TR4PWHFL*
Pinhole Flangeless



DCDHX-MUD-FL
Flangeless Mud Plate

*Requires Flangeless Mud Plate

FINISH OPTIONS

- White (WH)
- Black (BK)
- Clear Diffuse (CD)
- Warm Diffuse (WD)
- Black, White Flange (BW)
- Clear Diffuse, White Flange (CW)
- Warm Diffuse, White Flange (WW)
- Custom Color (CC)



- Customize your cylinder with over one million configurations
- Powered by DMF's advanced LED technology
- Modular Twist & Lock trims and Plug & Play light engines for easy maintenance and on-site modifications
- Shadowless pendant uplight allows for direct and indirect lighting from a single cylinder
- Die-cast aluminum with no visible hardware for a sleek, symmetrical design

Lumen Output 750 lm (10W), 1000 lm (12W), 1500 lm (20W), 2000 lm (28W), 2500 lm (37W), 3000 lm (40W)	Mount Surface, Cord, Stem, Wall	
Color Quality 90+ CRI, 2-step SDCM	Size Length: Small (4"), Medium (8"), Large (12") Diameter: 4"	
Color Temperatures <div><div><div>2700K</div><div>3000K</div><div>3500K</div></div><div><div>4000K</div><div>Warm Dim, 3000–1800K</div></div></div>	Finish White, Black, Brushed Aluminum, Bronze, Custom Color	
	Stem/Cord Length Standard: 24" or 48", Custom: Up to 96" Stem, Up to 156" Cord	
Lighting Type <div><div><div>Downlight</div><div>Up and downlight</div><div>Adjustable</div></div></div>	Beam Spread <div><div><div>15° Narrow Spot</div><div>25° Spot</div><div>40° Flood</div></div><div><div>60° Wide Flood</div><div>90°+ General Ambient</div></div></div>	
Emergency Lighting Optional Inverter or Emergency LED Driver with remote EM Test Switch for lighting up to 90 minutes in event of power failure		
1% Dimming TRIAC/ELV, 0-10V, Lutron EcoSystem	Input 120/277V	
Standards <div><div><div>JAB TITLE 24</div><div>ENERGY STAR</div><div>CERTIFIED US-CA</div><div>Declare.</div></div></div>	Trims and Shades Round Beveled Trim, Hyperbolic Trim, Snoot, Decorative Trim, Low-Profile Decorative Trim, Round Shade, Flat Shade	
	Ratings <div><div><div></div>Wet Location / IP65 Available</div></div>	Guarantee <div><div><div>50k HOURS</div><div>5 YEARS</div></div></div>

PRODUCT CODE

CYLINDER	DC4	4" Cylinder						
MOUNT	SM	Surface Mount	C2	Cord Mount, 24"	C4	Cord Mount, 48"	CC	Cord Mount, Custom
	T2	Stem Mount, 24"	T4	Stem Mount, 48"	TC	Stem Mount, Custom	WM	Wall Mount
CYLINDER OPTIONS	S	Standard	W	Wet Location				
SIZE	S	Small	M	Medium	L	Large		
LIGHT OPTIONS	D	Fixed	A	Adjustable				
LUMENS DOWN	07	750 lm	10	1000 lm	12	1250 lm	15	1500 lm
	20	2000 lm	25	2500 lm	30	3000 lm		
OPTICS DOWN	GA	General Ambient	NS	Narrow Spot	SP	Spot	FL	Flood
	WF	Wide Flood						
SPECIALTY LENS DOWN	0	None						
LUMENS UP	00	None	07	750 lm	10	1000 lm	12	1250 lm
	15	1500 lm	20	2000 lm				
OPTICS UP	00	None	GA	General Ambient	NS	Narrow Spot	SP	Spot
	FL	Flood	WF	Wide Flood				
CCT	27	2700K	30	3000K	35	3500K	40	4000K
	3W	Warm Dim						
FINISH	WH	White	BK	Black	BA	Brush Aluminum	BZ	Bronze
	CC	Custom Color						
DRIVER	T	TRIAC/ELV	O	0-10V	C	Lutron LDE1		
EMERGENCY OPTION	00	None	EM	Emergency Lighting with Remote Test Switch				
TRIM / SHADE DOWN	R	Round Beveled Trim	H	Hyperbolic Trim	S	Snoot	D	Decorative Trim
	L	Low Profile Decorative Trim	RWC	Round Shade: White, Clear	RWW	Round Shade: White, Warm	RBC	Round Shade: Black, Clear
	RBW	Round Shade: Black, Warm	RAC	Round Shade: Aluminum, Clear	RCC	Round Shade: Custom Color	FWC	Flat Shade: White, Clear
	FWW	Flat Shade: White, Warm	FBC	Flat Shade: Black, Clear	FBW	Flat Shade: Black, Warm	FCC	Flat Shade: Custom Color

ACCESSORIES

DCCX-RW	Round Beveled Trim, White
DCCX-RB	Round Beveled Trim, Black
DCCX-RA	Round Beveled Trim, Brushed Aluminum
DCCX-RZ	Round Beveled Trim, Bronze
DCCX-RC	Round Beveled Trim, Custom
DCCX-HW	Hyperbolic Trim, White
DCCX-HB	Hyperbolic Trim, Black
DCCX-HA	Hyperbolic Trim, Brushed Aluminum
DCCX-HZ	Hyperbolic Trim, Bronze
DCCX-HC	Hyperbolic Trim, Custom
DCCX-S	Snoot
DCCX-D	Decorative Trim
DCCX-L	Low-Profile Decorative Trim
DCCX-RWC	Round Shade: White Outside, Clear Diffused Inside
DCCX-RWW	Round Shade: White Outside, Warm Diffused Inside
DCCX-RBC	Round Shade: Black Outside, Clear Diffused Inside

DCCX-RBW	Round Shade: Black Outside, Warm Diffused Inside
DCCX-RAC	Round Shade: Brushed Aluminum Outside, Clear Diffused Inside
DCCX-RCC	Round Shade: Custom Color
DCCX-FWC	Flat Shade: White Outside, Clear Diffused Inside
DCCX-FWW	Flat Shade: White Outside, Warm Diffused Inside
DCCX-FBC	Flat Shade: Black Outside, Clear Diffused Inside
DCCX-FBW	Flat Shade: Black Outside, Warm Diffused Inside
DCCX-FAC	Flat Shade: Brushed Aluminum Outside, Clear Diffused Inside
DCCX-FCC	Flat Shade: Custom Color
DCCX-CC	Custom Length Cord Mount (up to 156")
DCCX-TC	Custom Length Stem Mount (up to 96")
DCCX-JW	Junction Box Cover, White
DCCX-JB	Junction Box Cover, Black
DCCX-JA	Junction Box Cover, Brushed Aluminum
DCCX-JZ	Junction Box Cover, Bronze
DCCX-JC	Junction Box Cover, Custom Color

H Series

Residential Lighting



- Brilliant illumination and reliable performance for your entire home
- Easily select ambient, general, or higher-ceiling illumination with the flip of a switch
- Accurate color rendering means people and home finishes look great
- Comfortable white light for accurate illumination at full brightness that transitions to a relaxing sunset effect at lower dimming levels

Application New Construction, Remodel, Retrofit	Compatible Housings H Series	Aperture 4", 3"
Brightness Switch Ambient Light: 350 lm (5W) 7-9 ft Ceiling: 750 lm (9W) 9-12 ft Ceiling: 950 lm (12W)	Color Quality 90+ CRI, 3-step SDCM	Input Voltage 120V
Dimming TRIAC/ELV 5%	Color Temperatures <div><div></div> Natural Warm Dim, 3000–2200K</div>	
Standards <div><div><div>JA8</div><div>TYPE 84</div></div><div><div>ENERGY STAR</div></div><div><div>UL</div><div>CERTIFIED</div><div>US-CA</div></div><div><div>Declare.</div></div></div>	Ratings <div><div><div></div>Type IC (Insulation Contact)</div><div><div></div>Air Tight</div><div><div></div>Suitable for Wet Locations</div></div>	Guarantee <div><div><div>50k</div><div>HOURS</div></div><div><div>5</div><div>YEARS</div></div></div>

PRODUCT CODE

PRODUCT	
HM3C	H Series Module with Natural Warm Dim

H Series

Residential Lighting

COMPATIBLE HOUSINGS & TRIMS

4" HOUSINGS & TRIMS



H4BH
4" New Construction
with Bar Hangers



H4SO
4" New Construction
with Wood Screws



H4RM
4" Remodel



H4TRSWH
4" Round



H4TRFWH
4" Flush



H4TSSWH
4" Square



H4TRAWH
4" Adjustable

3" HOUSINGS & TRIMS



H3BH
3" New Construction
with Bar Hangers



H3SO
3" New Construction
with Wood Screws



H3RM
3" Remodel



H3TRSWH
3" Round



H3TRFWH
3" Flush



H3TSSWH
3" Square



H3TRAWH
3" Adjustable

ADAPTERS




DRD2X-QCM-ED
Edison Adapter

FINISH OPTIONS

☐ White (WH)

DRD5S

4" Surface Mount



- Thinnest in its class, extends just 0.6" from the ceiling plane
- Clear uniform light, no dark spots
- 90+ CRI LED standard, and produces up to 1000 lumens of exceptional light
- Snaps into place for easy installation and maintenance
- Proprietary-integrated driver with smooth dimming capability down to 5%

Application New Construction, Retrofit	Compatible Housings SurfaceFrame, Metallic Octagonal or Non-Metallic Round Junction Box	
Delivered Lumens 750 lm (9.0W), 1000 lm (12.0W)	Input Voltage 120V for TRIAC/ELV 120/277V for 0-10V	
Color Quality 90+ CRI, < 3-step SDCM	Dimming TRIAC/ELV 5% 0-10V 1%	
Shape 4" Round, 4" Square	Finish White	
Color Temperatures <div><div></div><div></div><div></div><div>2700K3000K3500K</div></div>	Emergency Lighting Optional Emergency LED Driver with integrated EM Test Switch for lighting up to 90 minutes in event of power failure	
Standards <div><div><div>JA8</div><div>TITLE 24</div></div><div><div>ENERGY STAR</div></div><div><div>UL</div><div>CERTIFIED US-CA</div></div><div><div>Declare.</div></div></div>	Ratings <div><div></div><div>Wet Location</div></div>	Guarantee <div><div><div>50k</div><div>HOURS</div></div><div><div>5</div><div>YEARS</div></div></div>

PRODUCT CODE

PRODUCT		SIZE		SHAPE		LUMENS		CRI		CCT		DRIVER		OPTION	
DRD5S	Module	4	4" Width	R	Round	07	750 lm	9	90+ CRI	27	2700K	T	Integrated TRIAC/ELV	[Blank]	None
				S	Square	10	1000 lm			30	3000K	O	Integrated 0-10V	DF	Non-Conductive Dead Front
										35	3500K	EM	Emergency		

DRD5S

8" Round Surface Mount



- 8" round area light for lighting smaller spaces including bathrooms, closets, and kitchens
- Extends just 0.6" below the ceiling plane to minimize visual profile
- Integrated driver provides down to 5% dimming capability and simplifies maintenance

Application New Construction, Retrofit	Compatible Housings SurfaceFrame, Metallic Octagonal or Non-Metallic Round Junction Box	
Delivered Lumens 1500 lm (17W)	Input Voltage 120/277V	
Color Quality 90+ CRI, < 3-step SDCM	Dimming TRIAC/ELV 5% 0-10V 1%	
Shape 8" Round	Finish White	
Color Temperatures <div><div></div><div></div><div></div><div>2700K3000K3500K</div></div>	Emergency Lighting Optional Emergency LED Driver for lighting up to 90 minutes in event of power failure	
Standards <div><div><div>JA8</div><div>TITLE 24</div></div><div><div>ENERGY STAR</div></div><div><div>UL</div><div>CERTIFIED US-CA</div></div><div><div>Declare.</div></div></div>	Ratings <div><div></div><div>Wet Location</div></div>	Guarantee <div><div><div>50k</div><div>HOURS</div></div><div><div>5</div><div>YEARS</div></div></div>

PRODUCT CODE

PRODUCT		SIZE		SHAPE		LUMENS		CRI		CCT		DRIVER	
DRD5S	Module	8	8" Diameter	R	Round	15	1500 lm	9	90+ CRI	27	2700K	[Blank]	Integrated TRIAC/ELV
										30	3000K	O	Integrated 0-10V
										35	3500K	A	Alternate

DRD5S

18" Linear Surface Mount



- 18" x 4" linear area light perfect for narrow applications such as corridors or kitchen islands
- Extends just 0.6" below the ceiling plane to minimize visual profile
- Integrated driver provides down to 5% dimming capability and simplifies maintenance

Application New Construction, Retrofit	Compatible Housings SurfaceFrame, Metallic Octagonal or Non-Metallic Round Junction Box		
Delivered Lumens 1500 lm (17W)	Input Voltage 120/277V		
Color Quality 90+ CRI, < 3-step SDCM	Dimming TRIAC/ELV 5% 0-10V 1%		
Shape 18" x 4" Rectangle	Finish White		
Color Temperatures <div><div>2700K</div><div>3000K</div><div>3500K</div></div>	Emergency Lighting Optional Emergency LED Driver for lighting up to 90 minutes in event of power failure		
Standards <div><div>JA8</div><div>ENERGY STAR</div><div>CERTIFIED US-CA</div><div>Declare.</div></div>	Ratings <div><div>Wet Location</div></div>	Guarantee <div><div>50k HOURS</div><div>5 YEARS</div></div>	

PRODUCT CODE

PRODUCT	SIZE		SHAPE		LUMENS		CRI		CCT		DRIVER	
DRD5S	Module	4 4" Width	L	Linear	15	1500 lm	9	90+ CRI	27	2700K	[Blank]	Integrated TRIAC/ELV
									30	3000K	O	Integrated 0-10V
									30	3500K	A	Alternate

DRD5S

Surface Mount Series

INSTALLATION OPTIONS

DRD5S Installation Options




NEW CONSTRUCTION

SurfaceFrame Shallow Junction Box



DRDHNJO
New Construction
Fire Rated



DRDHNJO70SEM
Emergency
Fire Rated

RETROFIT

Compatible Junction Boxes



JUNCTION BOX	MIN. DEPTH	MIN. VOLUME	THROUGH-WIRE RATING
4O Octagonal (metallic)	2 1⁄8"	21.5 in³	6 (three in, three out) #12 AWG
3O Round (non-metallic)	2 3⁄4"	18 in³	6 (three in, three out) #12 AWG
4O Round (non-metallic)	2 3⁄16"	20 in³	6 (three in, three out) #12 AWG



DRD2

Fixed



DRD4

Adjustable



DCD3

Higher-Lumen Fixed



DCD4

Higher-Lumen Adjustable



H Series

Residential Lighting



DRD5S

Surface Mount Series

Application	New Construction, Remodel, Retrofit	New Construction, Remodel, Retrofit	New Construction, Remodel	New Construction, Remodel	New Construction, Remodel, Retrofit	New Construction, Retrofit
Housing	M Series; SurfaceFrame; Classic Frames 4", 5", 6", 8"; Cylinder	M Series; Classic Frames 4", 5", 6"; Cylinder	DCD Frame	DCD Frame	H Series	SurfaceFrame, Metallic Octagonal, or Non-Metallic Round Junction Box
Adjustment	–	360° directional aim, 45° tilt	–	360° directional aim, 40° tilt	–	–
Delivered Lumens	750 lm (9.5W), 1000 lm (12.5W), 1250 lm (14.3W), 1500 lm (17.5W)	750 lm (9.7 W), 1000 lm (12.0W)	1500 lm (20W), 2000 lm (28W), 2500 lm (37W), 3000 lm (40W)	1500 lm (21W), 2000 lm (37W), 2500 lm (40W)	Up to 950 lm (selectable 350 lm, 750 lm, 950 lm)	4": 750 lm (9.0W), 1000 lm (12.0W) 8"/18": 1500 lm (17.0W)
Efficacy	79 lm/W, 80 lm/W, 87 lm/W	82 lm/W	86 lm/W, 79 lm/W, 72 lm/W, 82 lm/W	70 lm/W, 60 lm/W, 67 lm/W	70 lm/W, 83 lm/W, 79 lm/W	83 lm/W
Color Quality	93+ CRI, 2-step SDCM	93+ CRI, 2-step SDCM	90+ CRI, 2-step SDCM	90+ CRI, 2-step SDCM	90+ CRI, 3-step SDCM	90+ CRI, < 3-step SDCM
Color Temperature	2700K, 3000K, 3500K, 4000K	2700K, 3000K, 3500K, 4000K	2700K, 3000K, 3500K, 4000K	2700K, 3000K, 3500K, 4000K	3000K	2700K, 3000K, 3500K
Warm Dim	3000K–1800K, 1000 lm (12.0W)	3000K–1800K, 1000 lm (12.0W)	–	–	3000K–2200K	–
Beam Spread	Narrow Spot (15°), Spot (25°), Flood (40°), Wide Flood (60°), General Ambient (90°+)	Narrow Spot (15°), Spot (25°), Flood (40°)	Narrow Spot (15°), Spot (25°), Flood (40°), Wide Flood (60°)	Narrow Spot (15°), Spot (25°), Flood (40°), Wide Flood (60°)	Flood	Flood
Options	Linear Spread, Soft Focus	Linear Spread, Black, White Surround, Soft Focus	–	Linear Spread	–	4" Round, 4" Square, 8" Round, 18" Linear
Input Voltage	120/277V	120/277V	120/277V	120/277V	120V	4": 120V for TRIAC/ELV or 120/277V for 0-10V; 8"/18": 120/277V
Dimming	TRIAC/ELV 1%, 0-10V 1%, Lutron® EcoSystem 1%	TRIAC/ELV 1%, 0-10V 1%, Lutron® EcoSystem 1%	0-10V 1%, Lutron® EcoSystem 1%	0-10V 1%, Lutron® EcoSystem 1%	TRIAC/ELV 5%	TRIAC/ELV 5%, 0-10V 1%
Emergency Lighting	Optional Emergency Driver	Optional Emergency Driver	Optional Emergency Driver	Optional Emergency Driver	–	Optional Emergency Driver
Standards	JA8 Title 24, UL Certified US-CA, ENERGY STAR®, Declare	JA8 Title 24, UL Certified US-CA, ENERGY STAR®, Declare	UL Certified US-CA, ENERGY STAR®, Declare	UL Certified US-CA, ENERGY STAR®, Declare	JA8 Title 24, UL Certified US-CA, ENERGY STAR®, Declare	JA8 Title 24, UL Certified US-CA, ENERGY STAR®, Declare
Ratings	Wet Location	Damp Location	Wet Location	Damp Location	Wet Location	Wet Location
Lifetime (L70)	50,000 hrs	50,000 hrs	50,000 hrs	50,000 hrs	50,000 hrs	50,000 hrs
Warranty	5 years	5 years	5 years	5 years	5 years	5 years



Brilliance, engineered

DMF designs and builds industry-leading modular downlighting that sets the bar for flexibility, performance, and quality. Our in-house R&D lab is filled with brilliant engineers always at work improving our products and inventing new ones. They understand that light is more than illumination; light is what makes a space beautiful, useful, and ultimately, enjoyable.

Every DMF product delivers exceptional performance and aesthetics, while also saving you time and money year after year. That same ethos drives every part of our company, from our tireless customer service to our fast, intelligent distribution. If you want lighting that's not just built better, but built smarter, DMF is the partner for you.

DMF Lighting

1118 East 223rd Street
Carson, CA 90745
323.934.7779
info@dmflighting.com
dmflighting.com